

## Deutsche Akkreditierungsstelle

### Annex to the Accreditation Certificate D-PL-12139-01-04 according to DIN EN ISO/IEC 17025:2018

**Valid from:** 28.03.2024

**Date of issue:** 01.08.2025

**This annex is a part of the Accreditation Certificate D-PL-12139-01-00.**

Holder of Accreditation Certificate:

**IMST GmbH**

**Carl-Friedrich-Gauß-Straße 2–4, 47475 Kamp-Lintfort**

with the location

**IMST GmbH**

**Prüfzentrum / Testcenter**

**Carl-Friedrich-Gauß-Straße 2–4, 47475 Kamp-Lintfort**

The testing laboratory meets the requirements of DIN EN ISO/IEC 17025:2018 to carry out the conformity assessment activities listed in this annex. The testing laboratory meets additional legal and normative requirements, if applicable, including those in relevant sectoral schemes, provided that these are explicitly confirmed below.

The management system requirements of DIN EN ISO/IEC 17025 are written in the language relevant to the operations of testing laboratories and they conform to the principles of DIN EN ISO 9001.

Tests in the field:

**Telecommunication (FCC Requirements)**

*This annex to the certificate was issued by the Deutsche Akkreditierungsstelle GmbH (DAkkS) and is digitally sealed.  
This annex to the certificate is only valid together with the written accreditation certificate and reflects the status as indicated by the date of issue. The current status of any valid and surveyed accreditation can be found in the directory of accredited bodies maintained by Deutsche Akkreditierungsstelle GmbH ([www.dakks.de](http://www.dakks.de)).*

**Annex to the Accreditation Certificate D-PL-12139-01-04**

Section	Scope	Test Method(s)	Frequency (max. assessed)
USA	RF Exposure - Devices subject to SAR requirements	IEEE Std 1528-2013 IEEE Recommended Practice for Determining the Peak Spatial-Average Specific Absorption Rate (SAR) in the Human Head from Wireless Communications Devices: Measurement Techniques  in combination with KDB Publication 865664 and in combination with KDB Publication 447498	Simulation Methods only;